

## RECHARGEABLE BATTERY DRAWER

**This rechargeable battery drawer has been specially designed for the AP2C, AP4C and TIMS**



It substitutes for the standard battery drawer, which uses the 2xLSH20 battery. It applies when the autonomy is reduced and when the conditions of extreme temperatures are less severe.

The rechargeable battery drawer is produced from rechargeable batteries using Hybrid Metal/Nickel (Ni/MH) technology. These batteries can be carried in any kind of plane without any particular restriction.

Note: The rechargeable battery drawer is a compact module that cannot be used with some accessories.

Recharge of the rechargeable battery drawer: The rechargeable battery drawer is refilled with a charger. It is supplied with 220V AC or 110V AC. It enables to recharge one rechargeable battery drawer at a time. The recharge operation lasts 2 hours.

<b>CHARACTERISTICS</b>	Standard battery drawer with 2xLSH20 battery block	Rechargeable battery drawer
Weight	305 gr (0.67 lb)	450 gr (1 lb)
Nominal tension	7 V	6 V
Maximum power	3 A	3 A
Nominal capacity	13 Ah	3,4 Ah
Range of operation	From -26°F to 131°F	From 14°F to 122°C
Range of storage	From -38°F to 160°F	From -38°F to 160°F
Autonomy:		
at + 20°C (68°F)	24h00	11h00
at + 50°C (122°F)	18h00	8h00
at + 0°C (32°F)	11h00	4h30
at - 10°C (14°F)	6h00	2h45
at - 32°C (-26°F)	3h00	Non operational

